

Fig. 1





Fig. 2



3 /9

Fig. 3A




Fig. 3B

3 2




Fig. 4

Diagram illustrating the relationship between two tables of device efficiency data (Fig. 4). The left table (41) shows data for cooling water temperatures of 8°C, 9°C, and 30°C. The right table (42) shows data for cooling water temperatures of 8°C, 9°C, and 30°C. Arrows indicate data flow or comparison between corresponding rows in the two tables.

COOLING WATER TEMPERATURE	DEVICE EFFICIENCY
8°C	0.978677579 0.976739177 0.976308421 0.975662287 0.974585397 0.974585397 0.974370019 0.973508507 0.973508507 0.973293129 0.973077751 0.973077751 0.973077751 0.971785484 0.971570106
9°C	0.983631273 0.982769761 0.982769761 0.982554383 0.981477493 0.981262115
30°C	0.966401034 0.96467801 0.964247254 0.96360112 0.96360112 0.963385742 0.96252423 0.959724316 0.957785914 0.95606289 0.95606289 0.954770622 0.954339866 0.952186087 0.951109197 0.950032307
31°C	0.954986

COOLING WATER TEMPERATURE	DEVICE EFFICIENCY
8°C	0.978677579 0.976739177 0.976308421 0.975662287 0.974585397 0.974585397 0.974370019 0.973508507 0.973508507 0.973293129
9°C	0.983631273 0.982769761 0.982769761 0.982554383 0.981477493 0.981262115
30°C	0.966401034 0.96467801 0.964247254 0.96360112 0.96360112 0.963385742 0.96252423 0.959724316 0.957785914 0.95606289
31°C	0.954986

5 / 9

Fig. 5A






Fig. 5B



6 /9

Fig. 6



7 / 9

Fig. 7

71

COOLING WATER TEMPERATURE	DEVICE EFFICIENCY	PLANT EFFICIENCY
8°C	0.976739177 0.974585397 0.976308421 0.974370019 0.973508507 0.978677579 0.975662287 0.973293129 0.973508507 0.974585397	0.992450073 0.985387238 0.979542133 0.979055041 0.978324403 0.977106673 0.976376035 0.973697029 0.970043838 0.9693132
9°C	0.981262115 0.982554383 0.982769761 0.983631273 0.982769761 0.981477493	0.980272772 0.979298587 0.976132489 0.967121286 0.960545543 0.87481734
.	.	.
.	.	.
.	.	.
.	.	.
30°C	0.964247254 0.954770622 0.951109197 0.95606289 0.952186087 0.968554814 0.96360112 0.96467801 0.959724316 0.95606289 0.963385742 0.957785914 0.96252423 0.954339866 0.96360112 0.950032307 0.966401034	1.006088651 0.997808086 0.990014613 0.987335606 0.985143692 0.970287384 0.970287384 0.9693132 0.965416464 0.96444228 0.964198734 0.963711642 0.961032635 0.960789089 0.959571359 0.95518753 0.943984413
31°C	0.954986	0.960545543

72

COOLING WATER TEMPERATURE	DEVICE EFFICIENCY	PLANT EFFICIENCY
8°C	0.976739177 0.974585397 0.976308421	0.992450073 0.985387238 0.979542133
9°C	0.981262115 0.982554383 0.982769761	0.980272772 0.979298587 0.976132489
.	.	.
.	.	.
.	.	.
30°C	0.964247254 0.954770622 0.951109197	1.006088651 0.997808086 0.990014613
31°C	0.954986	0.960545543

8 /9

Fig. 8A




Fig. 8B




Fig. 9 RELATED ART

